


optibelt KB

Optibelt KB kraftbands are made up of high quality wrapped single V-belts which are joined together with one another via a top surface. Depending on the task in hand, up to five wedge belts or classical V-belts are used per kraftband. In exceptional cases, kraftbands made up from more than five V-belts can be delivered. When using multiple kraftbands per drive, combinations of sets are required.

Optibelt kraftbands are distinguished by the following advantages:

- Single belt characteristics
- Favourable running behaviour with regards to vibrations
- Excellent flexibility
- Able to be clutched
- High level of operational safety
- V-flat drives

Optibelt KB kraftbands are used when dealing with extreme impact loads, large centre distances in connection with small pulley diameters and vertical shafts.



- 1 Rubber coating
- 2 Polyester tension cord
- 3 Base compound
- 4 Cover fabric

Sections:

3V/9J; 5V/15J; 8V/25J;
SPZ; SPA; SPB; SPC;
A/HA; B/HB; C/HC; D/HD

Dimensions:

1200 to 12 000 mm
standard range

Kraftband pulleys:

all standard pulleys
special pulleys on request

Examples of Applications

- | | |
|--------------------------|-----------------------------|
| Agricultural machines | Combine harvesters |
| Paper machines | Pulping machines |
| Plastics machines | Blenders |
| Construction machinery | Road milling machines |
| Conveying technology | Cargo container
machines |
| Wood processing machines | Gang saws |
| | Stone crushers |